




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G06F 9/45</b>		<b>A1</b>	(11) International Publication Number: <b>WO 95/09395</b>
			(43) International Publication Date: 6 April 1995 (06.04.95)
(21) International Application Number: <b>PCT/US94/10092</b>		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD).	
(22) International Filing Date: 9 September 1994 (09.09.94)			
(30) Priority Data: 127,585 27 September 1993 (27.09.93) US			
(71) Applicant: ORACLE CORPORATION [US/US]; 500 Oracle Parkway, Redwood City, CA 94065 (US).			
(72) Inventors: HALLMARK, Gary; 1503 Alta Glen Drive, San Jose, CA 95125 (US). LEARY, Daniel; 2500 Tunitas Creek Road, Half Moon Bay, CA 94019 (US).			
(74) Agents: HECKER, Gary, A. et al.; Hecker & Harriman, Suite 1200, 2049 Century Park East, Los Angeles, CA 90067 (US).			

**Published***With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.***(54) Title: METHOD AND APPARATUS FOR PARALLEL PROCESSING IN A DATABASE SYSTEM****(57) Abstract**

The present invention implements parallel processing in a Database Management System. The present invention provides the ability to locate transaction and recovery information at one location and eliminates the need for read locks and two-phased commits. The present invention provides the ability to dynamically partition row sources for parallel processing. Parallelism is based on the ability to parallelize a row source, the partitioning requirements of consecutive row sources and the entire row source tree, and any specification in the structured query language (SQL) statement. A Query Coordinator (802) assumes control of the processing of an entire query and can execute serial row sources (804, 806). Additional threads of control, Query Servers, execute parallel operators. Parallel operators are called data flow operators (DFOs). A DFO is represented as SQL statements and can be executed concurrently by multiple processes, or query slaves. A central scheduling mechanism, a data flow scheduler, controls a parallelized portion of an execution plan, and can become invisible for serial execution. Table queues are used to partition and transport rows between sets of processes. Node linkages provide the ability to divide the plan into independent lists that can each be executed by a set of query slaves. The present invention maintains a bit vector that is used by a subsequent producer to determine whether any rows need to be produced to its consumers. The present invention uses states and a count of the slaves that have reached these states to perform its scheduling tasks.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## METHOD AND APPARATUS FOR PARALLEL PROCESSING IN A DATABASE SYSTEM

### BACKGROUND OF THE INVENTION

#### 5 1. FIELD OF THE INVENTION

This invention relates to the field of parallel processing in a database environment.

#### 10 2. BACKGROUND ART

Sequential query execution uses one processor and one storage device at a time. Parallel query execution uses multiple processes to execute in parallel suboperations of a query. For example, virtually every query execution  
15 includes some form of manipulation of rows in a relation, or table of the DBMS. Before any manipulation can be done, the rows must be read, or scanned. In a sequential scan, the table is scanned using one process.

Parallel query systems provide the ability to break up the scan such that  
20 more than one process can perform the table scan. Existing parallel query systems are implemented in a shared nothing, or a shared everything environment. In a shared nothing environment, each computer system is comprised of its own resources (e.g., memory, central processing unit, and disk storage). Figure 1B illustrates a shared nothing hardware architecture. The  
25 resources provided by System one are used exclusively by system one. Similarly, system n uses only those resources included in system n.

Thus, a shared nothing environment is comprised of one or more autonomous computer systems that process their own data, and transmit a

- 2 -

result to another system. Therefore, a DBMS implemented in a shared nothing environment has an automatic partitioning scheme. For example, if a DBMS has partitioned a table across the one or more of the autonomous computer systems, then any scan of the table requires multiple processes to process the  
5 scan.

This method of implementing a DBMS in a shared nothing environment provides one technique for introducing parallelism into a DBMS environment. However, using the location of the data as a means for  
10 partitioning is limiting. For example, the type and degree of parallelism must be determined when the data is initially loaded into the DBMS. Thus, there is no ability to dynamically adjust the type and degree of parallelism based on changing factors (e.g., data load or system resource availability).

15 Further, using physical partitioning makes it difficult to mix parallel queries and sequential updates in one transaction without requiring a two phase commit. These types of systems must do two-phase commit because data is located on multiple disks. That is, transaction and recovery information is located on multiple disks. A shared disk logical software  
20 architecture avoids a two-phase commit because all processes can access all disks (see Figure 1D). Therefore, recovery information for updates can be written to one disk, whereas data accesses for read-only accesses can be done using multiple disks in parallel.

25 Another hardware architecture, shared everything, provides the ability for any resource (e.g., central processing unit, memory, or disk storage) to be available to any other resource. Figure 1A illustrates a shared everything hardware architecture. Figure 1A illustrates a shared everything hardware



- 3 -

architecture. All of the resources are interconnected, and any one of the central processing units (i.e., CPU 1 or CPU n) can use any memory resource (i.e., Memory 1 to Memory n) or any disk storage (i.e., Disk Storage 1 to Disk Storage n). However a shared everything hardware architecture cannot scale.

5. That is, a shared everything hardware architecture is feasible when the number of processors is kept at a minimal number of twenty to thirty processors. As the number of processors increases (e.g., above thirty), the performance of the shared everything architecture is limited by the shared bus (e.g., bus 102 in Figure 1A) between processors and memory. This bus has
- 10 limited bandwidth and the current state of the art of shared everything systems does not provide for a means of increasing the bandwidth of the shared bus as more processors and memory are added. Thus, only a fixed number of processors and memory can be supported in a shared everything architecture.

SUMMARY OF THE INVENTION

The present invention implements parallel processing in a Database Management System. The present invention does not rely on physical partitioning to determine the degree of parallelism. Further, the present invention does not need to use read lock, or require a two-phased commit in transaction processing because transaction and recovery information is located on multiple disks.

10 The present invention provides the ability to dynamically partition row sources for parallel processing. That is, partitioning identifies the technique for directing row sources to one or more query slaves. The present invention does not rely on static partitioning (i.e., partitioning based on the storage location of the data).

15 The present invention can be implemented using any architecture (i.e., shared nothing, shared disk, and shared everything). Further, the present invention can be used in a software-implemented shared disk system (see Figure 1D). A software-implemented shared disk systems is a shared nothing  
20 hardware architecture combined with a high bandwidth communications bus (bus 106 in Figure 1D) and software that allows blocks of data to be efficiently transmitted between systems.

A central scheduling mechanism minimizes the resources needed to  
25 execute an SQL operation. Further, a hardware architecture where processors do not directly share disk architecture can be programmed to appear as a logically shared disk architecture to other, higher levels of software via

- 5 -

mechanisms of passing disk input/output requests indirectly from processor to processor over high bandwidth shared nothing networks.

At compilation time, a sequential query execution plan is generated.

- 5 Then, the execution plan is examined, from the bottom up, to determine those portions of the plan that can be parallelized. Parallelism is based on the ability to parallelize a row source. Further, the partitioning requirements of consecutive row sources and the partitioning requirements of the entire row source tree is examined. Further, the present invention provides the ability
- 10 for the SQL statement to specify the use and degree of parallelism.

- A Query Coordinator (QC) process assumes control of the processing of a query. The QC can also execute row sources that are to be executed serially. Additional threads of control are associated with the QC for the duration of the
- 15 parallel execution of a query. Each of these threads is called a Query Server (QS). Each QS executes a parallel operator and processes a subset of intermediate or output data. The parallel operators that are executed by a QS are called data flow operators (DFOs).

- 20 A DFO is represented as an extended structured query language (SQL) statement. A DFO is a representation of one row source or a tree of row sources suitable for parallel execution. A DFO SQL statement can be executed concurrently by multiple processes, or query slaves. DFOs introduce parallelism into SQL operations such as table scan, order by, group by, joins,
- 25 distinct, aggregate, unions, intersect, and minus. A DFO can be one or more of these operations.

- 6 -

A central scheduling mechanism, a data flow scheduler, is allocated at compile time. When the top (i.e., root) of a row source tree, or a portion of a serial row source tree is encountered that cannot be implemented in parallel, the portion of the tree below this is allocated for parallelism. A data flow scheduler row source is allocated at compilation time and is executed by the QC process. It is placed between the serial row source and the parallelizable row sources below the serial row source. Every data flow scheduler row source and the parallelizable row sources below it comprise a DFO tree. A DFO tree is a proper subtree of the row source tree. A row source tree can contain multiple DFO trees.

If, at execution, the row source tree is implemented using parallelism, the parallelizer row source can implement the parallel processing of the DFOs in the row source tree for which it is the root node. If the row source tree is implemented serially, the parallelizer row source becomes invisible. That is, the rows produced by the row sources in the DFO tree merely pass through the parallelizer to the row sources above them in the row source tree.

The present invention uses table queues to partition and transport rows between sets of processes. A table queue (TQ) encapsulates the data flow and partitioning functions. A TQ partitions its input to its output according to the needs of the parent DFO and/or the needs of the entire row source tree. The table queue row source synchronously dequeues rows from a table queue. A TQ connects the set of producer slaves on its input to the set of consumer slaves on its output.

During the compilation and optimization process, each node in the row source tree is annotated with parallel data flow information. Linkages between

- 7 -

nodes in a row source tree provide the ability to divide the nodes into multiple lists. Each list can be executed by the same set of query slaves.

In the present invention only those processes that are not dependent on another's input (i.e., leaf nodes), and those slaves that must be executing to receive data from these processes execute concurrently. This technique of invoking only those slaves that are producing or consuming rows provides the ability to minimize the number of query slaves needed to implement parallelism.

10

The present invention includes additional row sources to facilitate the implementation of the parallelism. These include table queue, table access by partition, and index creation row sources. An index creation row source assembles sub-indices from underlying row sources. The sub-indices are serially merged into a single index. Row sources for table and index scanning, table queues, and remote tables have no underlying row sources, since they read rows directly from the database, a table queue, or a remote data store.

15

A table queue row source is a mechanism for partitioning and transporting rows between sets of processes. The partitioning function of a table queue row source is determined by the partitioning type of the parent DFO.

20

The present invention provides the ability to eliminate needless production of rows (i.e., the sorcerer's apprentice problem). In some cases, an operation is dependent on the input from two or more operations. If the result of any input operation does not produce any rows for a given consumer of that operation, then the subsequent input operation must not produce any

25

- 8 -

rows for that consumer. If a subsequent input operation were to produce rows for a consumer that did not expect rows, the input would behave erroneously, as a "sorcerer's apprentice."

5       The present invention uses bit vector to monitor whether each consumer process received any rows from any producer slaves. Each consumer is represented by a bit in the bit vectors. When all of the end of fetch (i.e. eof) messages are received from the producers of a consumer slave, the consumer sends a done message to a central scheduling mechanism (i.e., a data  
10 flow scheduler). The data flow scheduler determines whether the consumer slave received any rows, and sets the consumer's bit accordingly. The bit in the bit vector is used by subsequent producers to determine whether any rows need to be produced for any of its consumers. The bit vector is reset at the beginning of each level of the tree.

15

The dataflow scheduler uses states and a count of the slaves that have reached these states to perform its scheduling tasks. As the slaves asynchronously perform the tasks, transmitted to them by the dataflow scheduler, they transmit state messages to the dataflow scheduler indicating  
20 the stages they reach in these tasks. The data flow scheduler keeps track of the states of two DFOs at a time (i.e., the current DFO and the parent of the current DFO). A "started" state indicates that a slave is started and able to consume rows. A "ready" state indicates that a slave is processing rows and is about to produce rows. A "partial" state indicates that a slave is finished scanning a  
25 range of rowid, or equivalently, scanning a range of a file or files that contains rows, and needs another range of rowids to scan additional rows. "Done" indicates that a slave is finished processing.

### BRIEF DESCRIPTION OF THE DRAWINGS

Figures 1A~1D illustrates shared everything, shared nothing, and shared disk environments.

5

Figure 2 provides an example of database tables and an Structured Query Language query.

Figure 3A illustrates an example of a serial row source tree.

10

Figure 3B illustrates a parallelized row source tree.

Figure 3C illustrates a row source tree divided into levels each of which is implemented by a set of query slaves.

15

Figure 4 illustrates table queues.

Figure 5 illustrates a right-deep row source tree.

20

Figure 6A provides an example of parallelism annotation information.

Figure 6B provides an example of information sent to query slaves.

Figures 7A-7F illustrates slave DFOs process flows.

25

Figure 8 illustrates a row source tree including parallelizer row sources.

Figure 9 illustrates a three way join.

Figure 10A provides an Allocate Parallelizer process flow.

Figure 10B provides an example of the process flow for TreeTraversal.

5

Figure 11A illustrates a process flow for Fetch.

Figure 11B provides an example of the process flow of  
ProcessRowOutput.

10

Figure 11C illustrates a process flow of ProcessMsgOutput.

Figure 12 illustrates a Resume process flow.

15

Figure 13 illustrates a process flow for ProcessReadyMsg.

Figure 14 provides a process flow for NextDFO.

Figure 15 illustrates a process flow for Start.

20

Figure 16 illustrates a process flow for Close.

Figure 17 illustrates a process flow for SendCloseMsg.

25

Figure 18 illustrates a StartParallelizer process flow.

Figure 19 illustrates a Stop process flow.



- 11 -

### DETAILED DESCRIPTION OF THE INVENTION

A method and apparatus for parallel query processing is described. In the following description, numerous specific details are set forth in order to provide a more thorough description of the present invention. It will be apparent, however, to one skilled in the art, that the present invention may be practiced without these specific details. In other instances, well-known features have not been described in detail so as not to obscure the invention.

#### 10 ROW SOURCES

Prior to execution of a query, the query is compiled. The compilation step decomposes a query into its constituent parts. In the present invention, the smallest constituent parts are row sources. A row source is an object-oriented mechanism for manipulating rows of data in a relational database system (RDBMS). A row source is implemented as an iterator. Every row source has class methods associated with it (e.g., open, fetch next and close). Examples of row sources include: count, filter, join, sort, union, and table scan. Other row sources can be used without exceeding the scope of the present invention.

As a result of the compilation process, a plan for the execution of a query is generated. An execution plan is a plan for the execution of an SQL statement. An execution plan is generated by a query optimizer. A query optimizer compiles an SQL statement, identifies possible execution plans, and selects an optimal execution plan. One method of representing an execution plan is a row source tree. At execution, traversal of a row source tree from the

- 12 -

bottom up yields a sequence of steps for performing the operation(s) specified by the SQL statement.

A row source tree is composed of row sources. During the compilation process, row sources are allocated, and each row source is linked to zero, one, two, or more underlying row sources. The makeup of a row source tree depends on the query and the decisions made by the query optimizer during the compilation process. Typically, a row source tree is comprised of multiple levels. The lowest level, the leaf nodes, access rows from a database or other data store. The top row source, the root of the tree, produces, by composition, the rows of the query that the tree implements. The intermediate levels perform various transformations on rows produced by underlying row sources.

Referring to Figure 2, SQL statement 216 illustrates a query that involves the selection of department name 214 from department table 210 and employee name 206 from employee table 202 where department's department number is equal to the employee's department number. The result is to be ordered by employee name 206. The result of this operation will yield the employee name and the name of the department in which the employee works in order of employee.

An optimal plan for execution of SQL statement 216 is generated. A row source tree can be used to represent an execution plan. Figure 3A illustrates an example of a row source tree for this query 216. Row source tree 300 is comprised of row sources. Table scan row source 310 performs a table scan on the employee table to generate rows from the employee table. The output of table scan 310 is the input of sort 306. Sort 306 sorts the input by department

- 13 -

number. Table scan row source 312 performs a table scan on the department table to generate rows from the department table. The output of table scan 312 is the input of sort 308. Sort 308 sorts the input by department number.

- 5       The output from the two sort row sources (i.e., sort 306 and sort 308) is the input to sort/merge join row source 304. Sort/Merge join 304 merges the input from the employee table (i.e., the input from sort 306) with the input from the department table (i.e., the input from sort 308) by matching up the department number fields in the two inputs. The result will become the
- 10   output of sort/merge join 304 and the input of orderBy 302. OrderBy 302 will order the merged rows by the employee name.

#### DATA FLOW OPERATORS

- 15       A Query Coordinator (QC) assumes control of the processing of a query. The QC can also execute row sources that are to be executed serially. Additional threads of control are associated with the QC for the duration of the parallel execution of a query. Each of these threads is called a Query Server (QS). Each QS executes a parallel operator and processes a subset of the entire
- 20   set of data, and produces a subset of the output data. The parallel operators that are executed by a QS are called data flow operators (DFOs).

- A DFO is a representation of row sources that are to be computed in parallel by query slaves. A DFO for a given query is equivalent to one or more
- 25   adjacent row sources of that query's row source tree at the QC. Each DFO is a proper subtree of the query's row source tree. A DFO is represented as structured query language (SQL) statements. A DFO SQL statement can be executed concurrently by multiple processes, or query slaves. DFOs introduce

- 14 -

parallelism into SQL operations such as table scan, orderBy, group by, joins, distinct, aggregate, unions, intersect, and minus. A DFO can be one or more of these operations. A DFO is converted back into row sources at the query slaves via the normal SQL parsing mechanism. No additional optimization is

5 performed when DFO SQL is processed by the slaves.

An SQL table scan scans a table to produce a set of rows from the relation, or table. A "group by" (groupBy) rearranges a relation into groups such that within any one group all rows have the same value for the grouping

10 column(s). An "order by" (orderBy) orders a set of rows based on the values in the orderBy column(s). A join joins two or more relations based on the values in the join column(s) in the relations. Distinct eliminates any duplicate rows from the rows selected as a result of an operation.

15 Aggregates compute functions aggregated over one or more groups of rows. Count, sum and average aggregates, for example, compute the cardinality, sum, and average of the values in the specified column(s), respectively. Maximum (i.e. Max) and minimum (i.e., Min) aggregates compute the largest and smallest value (respectively) of the specified

20 column(s) among the group(s) of rows. A union operation creates a relation consisting of all rows that appear in any of two specified relations. An intersect operation creates a relation that consists of all rows that appear in both of two specified relations. A minus operation creates a relation that consists of all rows that appear in the first but not the second of two specified relations.

25

- 15 -

PARTITIONING

Existing parallel query systems are implemented in a shared nothing environment. Figure 1B illustrates a shared nothing hardware architecture.

- 5 In a shared nothing environment, each computer system is comprised of its own resources (e.g., memory, central processing unit, and disk storage). That is, a shared nothing environment is comprised of one or more autonomous computer systems, and each system processes its own data. For example, system one in Figure 1B is comprised of a central processing unit (i.e., CPU 1),  
10 memory (i.e., memory 1), and disk storage (i.e., disk storage 1). Similarly, system n contains similar resources.

A DBMS implemented in a shared nothing environment has an automatic partitioning scheme based on the physical location of data.

- 15 Therefore, partitioning, in a shared nothing environment, is determined at the time the physical layout of data is determined (i.e., at the creation of a database). Thus, any partitioning in a shared nothing environment is static.

- A scan of a table in a shared nothing environment necessarily includes a  
20 scanning process at each autonomous system at which the table is located. Therefore, the partitioning of a table scan is determined at the point that the location of data is determined. Thus, a shared nothing environment results in a static partitioning scheme that cannot dynamically balance data access among multiple processes. Further, a shared nothing environment limits the ability  
25 to use a variable number of scan slaves. A process, or slave, running in system one of Figure 1B can manipulate the data that is resident on system one, and then transfer the results to another system. However, the same process cannot operate on data resident on another system (i.e., system two through system n).

Thus, processes on each system can only process the data resident on its on system, and cannot be used to share the processing load at other systems.

Therefore, some processes can complete their portion of a scan and become

- 5 idle while other processes are still processing table scan tasks. Because each system is autonomous, idle processes cannot be used to assist the processes still executing a data access (e.g., table scan) on other systems.

The present invention provides the ability to dynamically partition data.

- 10 The present invention can be implemented using any of the hardware architectures (i.e., shared nothing, shared disk, or shared everything). Further, the present invention can be used in a software-implemented shared disk system. A software-implemented shared disk system is a shared nothing hardware architecture combined with a high bandwidth communications bus and software that allows blocks of data to be efficiently transmitted between
- 15 systems. Software implementation of a shared resource hardware architecture reduces the hardware costs connected with a shared resource system, and provides the benefits of a shared resource system.

- 20 Figure 1D illustrates a software-implemented shared disk environment, System one through system n remain autonomous in the sense that each system contains its own resources. However, a communications bus connects the systems such that data from system one through system n can transfer blocks of data. Thus, process, or slave, running in system one can perform
- 25 operations on data transferred from another system (e.g., system n).

In addition to the software-implemented shared disk environment, the present invention can be implemented in a shared everything hardware

- 17 -

architecture (illustrated in Figure 1A), and a shared disk hardware architecture (illustrated in Figure 1C). In the shared resource environments (Figures 1A, 1C, and 1D), any data is accessible by any process (e.g., shared disk and shared everything). Thus, multiple central processing units can access any data stored on any storage device. The present invention provides the ability to dynamically partition an operation (e.g., table scan) based on the amount of data instead of the location of the data.

For example, the present invention provides the ability to spread a table scan across "N" slaves to balance the load, and to perform a table scan on a table such that each slave finishes at virtually the same time. The present invention determines an optimal number of slaves, "N", to perform an operation. All "N" slaves can access all of the data. For example, a table can be divided into three groups of "N" partitions (i.e., "3N") using three groups of "N" ranges (i.e., "3N"). The ranges can be based on the values that identify the rows (i.e., entries) in a table. Further, the "3N" partitions are arranged based on size. Thus, there are "N" large partitions, "N" medium-sized partitions, and "N" small partitions. Each partition represents a partial execution of the scan operation.

20

The larger groups of rowids are submitted to the "N" slaves first. Each slave begins to process its rowid range. It is possible for some processes to complete their tasks before others (e.g., system resource fluctuations or variations in the estimations of partition sizes). When a process completes a partial execution, another set of rowid ranges can be submitted to the process. Since all of the large partitions were submitted to the "N" slaves at the start of a scan, faster slaves receive a medium or small rowid range partial execution. Similarly, as each slave completes its current rowid range, additional rowid

ranges can be submitted to the slave. Because decreasing sizes of rowid ranges are submitted to the faster slaves, all of the slaves tend to finish at virtually the same time.

## 5    – Partitioning Types –

The present invention provides the ability to dynamically partition using any performance optimization techniques. For example, prior to the execution of an operation to sort a table (i.e., order by), a sampling can be  
10    performed on the data in the table. From the results of the sampling, even distributions of the rows can be identified. These distributions can be used to load balance a sort between multiple processes.

Some examples of partitioning include range, hash, and round-robin.  
15    Range partitioning divides rows from an input row source to an output row source based on a range of values (e.g., logical row addresses or column value). Hash partitioning divides rows based on hash field values. Round-robin partitioning can divide rows from an input row source to an output row source when value based partitioning is not required. Some DFOs require  
20    outputs to be replicated, or broadcast, to consumers, instead of partitioned.

## PLAN PARALLELIZATION

A serial execution plan (e.g., Figure 3A) provides a non-parallelized  
25    representation of a plan for execution of a query. In serial query processing, only one thread of control processes an entire query. For example, a table scan of the employee table (i.e., table scan 310 in Figure 3A), for example, is scanned sequentially. One process scans the employee table.



The parallelism of the present invention provides the ability to divide an execution plan among one or more processes, or query slaves. Parallel query execution provides the ability to execute a query in a series of parallel steps, and to access data in parallel. For example, a table scan of the employee table can be partitioned and processed by multiple processes. Therefore, each process can scan a subset of the employee table.

At compilation time, a sequential query execution plan is generated. Then, the execution plan is examined, from the bottom up, to determine those portions of the plan that can be parallelized. Parallelism is based on the ability to parallelize a row source. Further, the partitioning requirements of consecutive row sources and the partitioning requirements of the entire row source tree is examined. Further, the present invention provides the ability for the SQL statement to specify the use and degree of parallelism.

The present invention provides the ability to combine parallelism and serialism in the execution of a query. Parallelism may be limited by the inability to parallelize a row source. Some row sources cannot be parallelized. For example, an operation that computes row numbers must allocate row numbers sequentially. When a portion of a row source tree is encountered that cannot be implemented in parallel, any portion below the serial row source is allocated for parallelism. A parallelizer row source is allocated between the serial row source and the parallelizable row sources below the serial row source. The parallelizer row source and the parallelizable row sources below it comprise a DFO tree. The output of this DFO tree is then supplied as input to the serial row source. A row source tree can contain multiple DFO trees.

If, at execution, a given row source tree is implemented using parallelism, the parallelizer row source can implement the parallel processing of the parallelizable DFOs in the row source tree for which it is the root node.

- 5 If the row source tree is implemented serially, the parallelizer row source becomes invisible. That is, the rows produced by the row sources in the DFO tree merely pass through the parallelizer row source to the row sources above it in the row source tree.
- 10 The row source tree is examined to determine the partitioning requirements between adjacent row sources, and the partitioning requirements of the entire row source tree. For example, the presence of an orderBy row source in a row source tree requires that all value based partitioning in the row source tree below the orderBy must use range partitioning instead of hash
- 15 partitioning. This allows the orderBy to be identified as a DFO, and its operations parallelized, since ordered partitioning of the orderBy DFO's output will then produce correct ordered results.

- An orderBy operation orders the resulting rows (i.e., the output from
- 20 the executed plan) according to the orderBy criteria contained in the SQL statement represented by the execution plan. To parallelize an orderBy operation, the query slaves that implement the operation each receive rows with a range of key values. Each query can then order the rows within its range. The ranges output by each query slave (i.e., the rows ordered within
  - 25 each range) can then be concatenated based on the orderBy criteria. Each query slave implementing the orderBy operation expects row sources that fall within the range specification for that query slave. Thus, the operations performed

- 21 -

prior to the orderBy operation can be performed using range partitioning to facilitate the direction of the rows according to the range specification.

Figure 3B illustrates a row source tree in which parallelism has been introduced. Table scan 310 in Figure 3A is processed by a single process, or query slave. In Figure 3B, table scan 310 is partitioned into multiple table scans 330A-330C. That is, the table scan of the employee table is processed by multiple process, or query slaves.

Figure 3B represents a parallel DFO tree corresponding to the row source tree depicted in Figure 3A. Sort 306 and sort 308 of Figure 3A are combined with sort/merge join 304 to distinguish the sort/merge join DFO of Figure 3B. Referring to Figure 3B, slave DFOs 324A-324C perform the sort and join operations. The output of slave DFOs 330A-330C is transmitted to slave DFOs 324A-324C.

Table scan 332 scans a table (i.e., department table) that does not contain many rows. Thus, the application of parallelism to scan the department table may not improve performance. Therefore, table scan 332 can be implemented as a non-parallel scan of the department table. The output of table scan 332 becomes the input of slave DFOs 324A-324C.

An SQL statement can specify the degree of parallelism to be used for the execution of constituent parts of an SQL statement. Hints incorporated in the syntax of the statement can be used to affect the degree of parallelism. For example, an SQL statement may indicate that no amount of parallelism is to be used for a constituent table scan. Further, an SQL statement may specify the

- 22 -

maximum amount of partitioning implemented on a table scan of a given table.

### TABLE QUEUES

5

Some DFOs function correctly with any arbitrary partitioning of input data (e.g., table scan). Other DFOs require a particular partitioning scheme. For example, a group by DFO needs to be partitioned on the grouping column(s). A sort/merge join DFO needs to be partitioned on the join column(s). Range partitioning is typically chosen when an orderBy operation is present in a query. When a given child DFO produces rows in such a way as to be incompatible with the partitioning requirements of its parent DFO (i.e., the DFO consuming the rows produced by a child DFO), a table queue is used to transmit rows from the child to the parent DFO and to repartition those rows to be compatible with the parent DFO.

15

The present invention uses a table queue to partition and transport rows between sets of processes. A table queue (TQ) encapsulates the data flow and partitioning functions. A TQ partitions its input to its output according to the needs of the consumer DFO and/or the needs of the entire row source tree. The table queue row source synchronously dequeues rows from a table queue. A TQ connects the set of producers on its input to the set of consumer slaves on its output.

20

A TQ provides data flow directions. A TQ can connect a QC to a QS. For example, a QC may perform a table scan on a small table and transmit the result to a table queue that distributes the resulting rows to one or more QS threads. The table queue, in such a case, has one input thread and some

25

- 23 -

number of output threads equaling the number of QS threads. A table queue may connect some number, N, of query slaves to another set of N query slaves. This table queue has N input threads and N output threads. A table queue can connect a QS to a QC. For example, the root DFO in a DFO tree writes to a table queue that is consumed by the QC. This type of table queue has some number  
5 of input threads and one output thread.

Figure 4 illustrates table queues using the parallel execution plan of SQL statement 216 in Figure 2. Referring to Figure 3B, the output of the table scans  
10 330A-330C becomes the input of sort/merge join DFOs 324A-324C. A scan of a table can be parallelized by partitioning the table into subsets. One or more subsets can be assigned to processes until the maximum number of processes are utilized, or there are no more subsets.

15 While an ordering requirement in an SQL statement may suggest an optimal partitioning type, any partitioning type may be used to perform a table scan because of the shared resources (e.g., shared disk) architecture. A table queue can be used to direct the output of a child DFO to its parent DFO according to the partitioning needs of the parent DFO and/or the entire row  
20 source tree. For example, table queue 406 receives the output of table scan DFOs 402A-402C. Table queue 406 directs the table scan output to one or more sort/merge join DFOs 410A-410C according to the partitioning needs of DFOs 410A-410C.

25 In some instances, there is virtually no benefit in using parallel processing (e.g., table scan of a table with few rows). Referring to Figure 4, table scan 412 of a small table (i.e., department table) is not executed in parallel. In the preferred embodiment, a table scan performed by a single process is

- 24 -

performed by QC 432. Thus, the input to table queue 416 is output from QC 432. Table queue 416 directs this output to the input of DFOs 410A-410C. Table queue 416 connects QC 432 to QS slave DFOs 410A-410C. The input from table queues 406 and 416 is used by DFOs 410A-410C to perform a sort/merge join operation.

The output of DFOs 410A-410C is transmitted to table queue 420. Table queue 420 directs the output to DFOs 424A-424C. The existence of an orderBy requirement in an SQL statement requires the use of a type of range partitioning for table queue 420, and is suggested for range partitioning of TQ 406 and 416. Range partitioning will result in row partitions divided based on sort key value ranges. In the present example, SQL statement 216 in Figure 2 specified an order in which the selected rows should be provided (i.e., ordered by employee name). Therefore, range partitioning is the partitioning scheme to execute SQL statement 216 in parallel. Thus, table queue 420 can direct a set of rows to each of the query slaves executing DFOs 424A-424C based on a set of ranges. Range partitioning can be used to divide the rows, by value ranges, between the query slaves processing the rows.

## 20 DFO SQL

A DFO is represented as structured query language (SQL) statements. For example, block 216 in Figure 2 illustrates a selection operation from employee and department tables. A selection operation includes a scan operation of these tables. The DFO SQL for the employee table scan is:

```
select /*+ rowid(e) */ deptno c1, empname c2
  from emptable
 where rowid between :1 and :2
```

-25-

The ":1" and ":2" are rowid variables that delimit a rowid range. Actual rowid values are substituted at the beginning of execution. As each slave completes the scanning of a rowid range (i.e., completion of a partial  
5 execution), additional rowid values are substituted at each subsequent partial execution. The scan produces the department field and employee name values.

The DFO SQL statement above illustrates extensions of SQL that provide  
10 the ability to represent DFOs in a precise and compact manner, and to facilitate the transmission of the parallel plan to multiple processes. One extension involves the use of hints in the DFO SQL statement that provide the ability to represent a DFO in a precise and compact way. In addition to the hint previously discussed to specify the use and/or degree of parallelism, the  
15 present invention provides the ability to incorporate hints in a DFO SQL statement to specify various aspects of the execution plan for the DFO SQL statement. For example, in the previous DFO SQL statement, the phrase "/\*+ rowid(e) \*/" provides a hint as to the operation of the table scan DFO (i.e., use rowid partitioning). Other examples are: "full" (i.e., scan entire table),  
20 "use\_merge" (i.e., use a sort/merge join), and "use\_nl" (i.e., use a nested loop join).

Another extension provides the ability to use and reference table queues. The output of the employee table scan is directed to a table queue (e.g.,  
25 Q1) as illustrated in Figure 4. The contents of table queue Q1 become the input to the next operation (i.e., sort/merge). The DFO SQL statement assigns aliases for subsequent references to these fields. The DFO statement further creates a reference for the columns in the resulting table queue (i.e., "c1" and "c2").

- 26 -

These "aliases" can be used in subsequent SQL statements to reference the columns in any table queue.

A second table scan is performed on the department table. As illustrated previously, because the department table is small (i.e., a lesser number of table entries), the department table scan can be performed serially. The output of the department table scan is directed to the Q0 table queue. The contents of Q0 table queue becomes the input to the sort/merge operation.

10 The DFO SQL for the sort/merge operation is:

```
select /*+ use_merge(a2) */ a1.c2, a2.c2
  from :Q1 a1, :Q0 a2
 where a1.c1 = a2.c1
```

15 The sort/merge DFO SQL operates on the results of the employee table scan (i.e., Q1 table queue, or "a1"), and the results of the department table scan (i.e., Q0 table queue, or "a2"). The output of the sort/merge join DFO is directed to table queue Q2 as illustrated in Figure 4. The contents of table queue Q2 becomes the input to the next operation (i.e., orderBy). The DFO SQL  
20 for the orderBy operation is:

```
select c1, c2 from :Q2 order by c1
```

The orderBy operation orders the results of the sort/merge join DFO.  
25 The output of the orderBy operation is directed to the requester of the data via table queue Q3.



- 27 -

COMBINED DFOs

If the partitioning requirements of adjacent parent-child DFOs are the same, the parent and child DFOs can be combined. Combining DFOs can be done using the SQL mechanism. For example, a reference to a table queue in a SQL statement (e.g., Qn) is replaced with the SQL text that defines the DFO. For example, if block 216 in Figure 2 specified "order by deptNo," the sort/merge join and the orderBy operations can be combined into one DFO SQL. Thus, the first two statements can be combined to be statement three:

```

10
      1.  select /*+ ordered use_merge(a2) */ a1.c2, a2.c2, a2.c2
           from :Q1 a1, :Q0 a2
           where a1.c1 = a2.c1
      2.  select c2, c3 from :Q2 order by c1
15      3.  select c2, c3
           from (select /*+ ordered use_merge(a2) */ a1.c1 c1, a1.c2 c2,
                  a2.c2 c3
           from :Q1 a1, :Q0 a2
           where a1.c1 = a2.c1)
20      order by c1

```

PLAN ANNOTATIONS

During the compilation and optimization process, each node in the row source tree is annotated with parallel data flow information. Figure 6A provides an example of parallelism annotation information. If the node is a DFO, the type of DFO is retained (e.g., table scan, sort/merge join, distinct, and orderBy). If the node is a serial row source to be processed by the QC, the table

- 28 -

queue to which the QC outputs the rows generated from the execution of the row source is stored with the other information associated with the row source. A node that represents a DFO also contains information regarding the DFO.

5

The number of query slaves available at the time of execution effects the degree of parallelism implemented. The number of available processes may be affected by, for example, quotas, user profiles, or the existing system activity. The present invention provides the ability to implement any degree of parallelism based on the number of query slaves available at runtime. If enough query slaves are available, the degree of parallelism identified at compile time can be fully implemented. If some number less than the number needed to fully implement the degree of parallelism identified at compile time, the present invention provides the ability to use the available query slaves to implement some amount of parallelism. If the number of available query slaves dictates that the query be implemented serially, the present invention retains the row source equivalent for each node. Thus, the present invention provides the ability to serially implement a query parallelized at compile time.

20

If the node is implemented by the QC, the output table queue identifier is included in the node information. If the node is not implemented by the QC, the pointer to the first child of the parallelized node, the number of key columns in the input table queue, the parallelized node's partitioning type, and the number of columns clumped with parent are included in the node information.

25

- 29 -

If the node represents a table scan DFO, the information includes table scan information such as table name and degree of parallelism identified for the scan. If the DFO is an indexed, nested loop join, the information includes the right and left input table names. If the DFO is a sort/merge join, the information includes two flags indicating whether the operation is a merge join or an outer join. If the DFO represents an index creation, the information includes a list of columns included in the index, the index type, and storage parameters.

At the time of implementation, information describing the DFOs is sent to the query slaves implementing the DFOs. All DFOs of an even depth are sent to one slave set. All DFOs of an odd depth are sent to the other slave set. Depth is measured from the top (root) node of the tree. Figure 6B provides an example of information sent to query slaves. This information includes a pointer to the next DFO for the slave set to execute. The next-to-execute pointer points to the next DFO at the same depth, or, if the current DFO is the last at its depth, the pointer points to the leftmost DFO in the tree at depth-2. The next-to-execute pointer links the DFOs not implemented by the QC into a set of subtrees, or lists.

20

Using the next-to-execute pointer, a row source tree can be split into two DFO lists that can be executed by two sets of query slaves. The DFOs executed by a first set of query slaves is given by a list starting with the leftmost leaf of the DFO tree and linked by the next-to-execute pointers. The DFOs executed by a second set of query slaves is given by the list starting with the parent of the leftmost leaf and linked by another set of sibling pointers.

25

- 30 -

The present invention can be implemented without a central scheduling mechanism. In such a case, all of the slaves needed to implement the DFOs are implemented at the start of execution of the row source tree.

However, many of the slaves must wait to begin processing (i.e., remain idle) until other slaves supply data to them.

In the preferred embodiment of the present invention, a central scheduling mechanism is used to monitor the availability of data, and to start slaves as the data becomes ready for processing by the slaves. Therefore, the only slaves that are started are those that can begin processing immediately (i.e., leaf nodes), and those slaves that must be executing to receive data from the leaf nodes. This technique of invoking only those slaves that are producing or consuming rows provides the ability to minimize the number of query slaves needed to implement parallelism.

For example, a first set of query slaves can be used to produce rows for a second set of query slaves. Once the first set (i.e., the producing set of query slaves) completes its task of producing rows, the set can be used to implement the DFOs that consume the output from the second set of query slaves. Once the second set of slaves completes its task of producing rows for the first set, the set can be used to implement the level of the tree that receives input from the first set. This technique of folding the DFO tree around two sets of slave sets minimizes the number of slaves needed to implement a tree. As the depth of the tree increases, the savings in processing power increases. Further, this technique provides the ability to implement an arbitrarily complex DFO tree.

- 31 -

Figure 3C illustrates a row source tree divided into thirds (i.e., Sets A-C) by lines 340 and 342 representing the levels of the tree that can be implemented by one set of query slaves. For example, Set A includes DFOs 330A-C and DFOs 344A-344C. These DFOs can be processed by a first slave set (i.e., slave set A).

5

The query slaves in slave set A perform table scans on an employee table and a department table. The rows generated by these tables scans are the output of slave set A. The output of slave set A becomes the input of the query slaves in set B. Thus, the query slaves in set B must be ready to receive the output from slave set A. However, the query slaves implementing the operations in set C do not have to be invoked until slave set B begins to generate output. Slave set B must sort and merge the rows received from slave set A. Therefore, output from slave set B cannot occur until after slave set A has processed all of the rows in the employee and department tables.

10 Therefore, once slave set A finishes processing the DFOs in set A, slave set A is available to implement the DFOs in set C. Therefore, the implementation of tree 350 only requires two slave sets (slave set A and B).

15

Referring to Figure 6B, information sent to query slaves include the output TQ identifier, the number of rowid-partitioned tables, the size of the SQL statement representing the DFO, the SQL statement representing the DFO, and flags that define runtime operations (e.g., slave must send "Started" message, slave sends "Ready" message when input consumed, and close slave expects to be closed upon completion).

25

Additional row sources facilitate the implementation of the parallelism of the present invention. These include parallelizer, table queue, table access by partition, and index creation row sources. An index creation row source

- 32 -

assembles sub-indices from underlying row sources. The sub-indices are serially merged into a single index. Row sources for table and index scanning, table queues, and remote tables have no underlying row sources, since they read rows directly from the database, a table queue, or a remote data store.

5

A table queue is a mechanism for partitioning and transporting rows between sets of processes. The input TQ function of a table queue is determined by the partitioning type of the parent DFO. The following are examples of some considerations that can be used to determine the type of TQ partitioning:

10

1. The inputs to a DFO must be hash partitioned, if the DFO requires value partitioning (e.g., a sort/merge join or group by), there is no orderBy in the DFO tree, and the DFO is not a nested loop join;

15

2. The inputs to a DFO must be range partitioned, if the DFO requires value partitioning (e.g., a sort/merge join or group by), there is an orderBy in the DFO tree, and the DFO is not a nested loop join;

20

3. If the DFO is a nested loop join, one input must be arbitrarily partitioned and the other input must access all of the input data either by using a broadcast TQ or a full table scan;

25

4. When rows are returned to the QC, partitions must be returned sequentially and in order, if the statement contains an orderBy. Otherwise, the rows returned from the partitions can be interleaved;

- 33 -

### DATA FLOW SCHEDULER

The parallelizer row source (i.e., data flow scheduler) implements the parallel data flow scheduler. A parallelizer row source links each DFO to its parent using a TQ. If parallelism cannot be implemented because of the unavailability of additional query slaves, the parallelizer row source becomes invisible, and the serial row source tree is implemented. In this instance, the parallelizer is merely a conduit between the underlying row source and the row source to which the parallelizer is the underlying row source. In general, row sources are encapsulated and, therefore, do not know anything about the row sources above or below them.

### PARALLELIZER ALLOCATION

At compilation, when you reach a row source that is the top of a DFO tree, or is directly below a portion of the row source tree that cannot be parallelized, a parallelizer row source is allocated between the top of the DFO tree and below the serial portion of the row source tree. Figure 8 illustrates a row source tree including parallelizer row sources. Parallelizer 808 is allocated between DFO subtree 810 and serial row source 806. Parallelizer 812 is allocated between DFO subtree 812 and serial row source tree 804.

Figure 10A provides an Allocate Parallelizer process flow. Processing block 1002 gets the root DFO in the DFO tree and initializes flags. At processing block 1004, the number of table instances scanned is determined. At processing block 1006, the number of table queues is determined. The number of table queues receiving rows from serially processed nodes is determined at processing block 1008.

At decision block 1010 (i.e., "orderBy in query?"), if an orderBy is present in the SQL statement being processed, an orderBy flag is set, and processing continues at decision block 1014. If an orderBy is not present in the SQL statement, processing continues at decision block 1014. At decision block 1014 (i.e., "close message needed?"), if a close message must be sent to the slaves, a close flag is set, and processing continues at processing block 1018. If no close message is needed, processing continues at processing block 1018.

At processing block 1018, redundant columns that are not key columns are eliminated from the SQL statement(s). The start and ready synchronization requirements (i.e., whether slaves need to communicate started and ready states to the data flow scheduler) are determined and retained at block 1020. At processing block 1022, the maximum depth of the tree is determined by examining the tree. At 1024, TreeTraversal is invoked to traverse the DFO tree for which the current parallelizer row source is being allocated. Processing ends at processing block 1026.

TreeTraversal is invoked to further define the execution environment for a DFO tree. Figure 10B provides an example of the process flow for TreeTraversal. At processing block 1032, the table queue identifier (TQ ID) is initialized to zero, and the starting TQ ID for parallel DFOs is determined. At decision block 1034 (i.e., "all nodes processed?"), if the tree has been traversed, processing returns to AllocateParallelizer at block 1036. If the traversal is not complete, processing continues at block 1038. The first, or next node in the execution order is identified at processing block 1038.



- 35 -

At processing block 1040, the TQ connection code (i.e., from slave set 1 to slave set 2, or from slave set 2 to slave set 1, or from QC to slave set 1, or from slave set 1 to QC, or from QC to slave set 2, or from slave set 2 to QC) is determined, and the TQ's partitioning type is determined. At processing block 5 1044, a TQ ID is assigned to the TQ, and the TQ ID counter is incremented. At decision block 1046 (i.e., "table scans?"), if there are no table scans in the DFO, processing continues at decision block 1046. If there are table scans, the number of distinct tables scanned is determined, and the index of distinct tables for this DFO is allocated and initialized at processing block 1046.

10 Processing continues at decision block 1050.

At decision block 1050 (i.e., "node to be executed by slave set 1 or slave set 2?"), if the node is executed by slave set 1, processing continues at decision block 1052. At decision block 1052 (i.e., "node first in execution chain 1?"), if 15 the node is the first to be executed in the first chain, this node is set as the current node at processing block 1054, and processing continues at block 1058. If the node is not the first to be executed, the next node pointer of the previous node in this chain is set to point to the current node at processing block 1056, and processing continues at block 1058.

20

If, at decision block 1050, the node is to be executed by slave set 2, processing continues at decision block 1072. At decision block 1072 (i.e., "node first in execution chain 2?"), if the node is the first to be executed in the second chain, this node is set as the current node at processing block 1074, and 25 processing continues at block 1058. If the node is not the first to be executed, the next node pointer of the previous node in this chain is set to point to the current node at processing block 1076, and processing continues at block 1058.

- 36 -

At processing block 1058, the partitioning type for the TQ is determined. At processing block 1060, the table queue format is initialized. At processing block 1062 the table queue descriptor is allocated. At processing block 1062, the table queue descriptor contains information regarding the TQ including the TQ ID, partitioning type, and connection code. The SQL for the DFO is generated at processing block 1064. Processing continues at decision block 1034 to process any remaining nodes of the tree.

### PARALLELIZER INITIATION

10

After an SQL statement is compiled and an execution plan is identified, the SQL statement can be executed. To execute an SQL statement, execution begins from the top of the row source tree. From the root down, each node is told to perform one of its operations (e.g., open, fetch, or close). As each node begins its operations, it must call upon its underlying nodes to perform some prerequisite operations. As the tree is traversed in this manner, any parallelizer row sources that are encountered are called upon to implement its functionality (i.e., start).

20

Operations (e.g., fetching rows from DBMS) can be performed more than once. This results in multiple calls to a parallelizer. When a parallelizer is called after a first call to the parallelizer, the parallelizer must be able to determine the state of the slaves implementing the underlying DFO tree (e.g., the state of the slaves, what DFOs are running). StartParallelizer, illustrated in Figure 18, provides an example of the steps executed when a parallelizer row source is called.

25

- 37 -

At block 1802, flags are initialized (e.g., opened, started, no row current, and not end of fetch). At decision block 1804 (i.e., "restart with work in progress?"), if the parallelizer was not restarted with work in progress, processing continues at block 1808. Processing continues at block 1808 to set the  
5 maximum number of slaves to the maximum number of slaves allowed (i.e., based on a system's limitations) per query.

At decision block 1810 (i.e., "rowid ranges set?"), if rowid ranges are set, processing continues at block 1814. If the rowid ranges have not been set,  
10 processing continues at block 1812 to allocate rowid ranges per slave, and processing continues at block 1814. At processing block 1814, the rowid ranges and the slave processes to implement the underlying DFO tree are allocated. At decision block 1816 (i.e., "any slaves available?"), if no slaves are available for allocation to perform the parallelism of the underlying DFO tree,  
15 processing continues at block 1834 to clear flags in output TQ, and at 1836 to start the underlying serial row source. Thus, where system limitations do not permit any parallelism, the parallelizer initiates the serial row source tree to implement the functionality of the parallel DFO tree. Processing returns at block 1834.

20

If some amount of parallelism is available, processing continues at decision block 1818. At decision block 1818 (i.e., "first execute?"), if this is the first execution of the parallelizer, processing continues at block 1820 to initialize working storage (e.g., allocate variable length items from the cursor  
25 work heap, allocate and initialize bind value pointers, allocate and initialize TQ data structures, allocate SMJ TQ consumer bit vector, and allocate partial execution bit vector). Processing continues at decision block 1822.

- 38 -

If this is not the first execution of the parallelizer, processing continues at decision block 1822. At decision block 1822 (i.e., "SQL statement parsing necessary?"), if the parsing is required, processing continues at block 1824 to compile and bind DFO SQL statement at all of the slaves. Processing continues  
5 at block 1826. If parsing is not necessary, processing continues at block 1826.

At block 1826, the current node is set to the first node to be executed (i.e., the bottom-most, left-most node of the DFO tree). At block 1828, the current node's and its' parent's slave count is set to zero, the current node's and its'  
10 parent's state is set to NULL. At block 1830, the TQ bit vector is set, the partial execution bit vector is cleared, and the row counter is set to zero. At 1832, Start is invoked to start the current DFO. Processing ends at block 1834.

-- Start Node --

15

At various stages of implementation of a DFO tree, the parallelizer (i.e., data flow scheduler) traverses the DFO tree, using the DFO tree pointers, to find the next node to implement. When a node is identified that is not already started, the parallelizer starts the node. Figure 15 illustrates a process flow for  
20 Start.

At decision block 1502 (i.e., "Nodes serially processed?"), processing continues at block 1504. At block 1504, the node is started. At block 1506, the fact that no ready message is needed is indicated (i.e., slaves will continue to  
25 process without ready synchronizations from the parallelizer). The counter is set to the number of slaves implementing the node at block 1508. Processing continues at block 1510.

- 39 -

If, at decision block 1502, parallelism can be used to implement the node, processing continues at block 1520. At block 1520, the slave counter is set to zero. At decision block 1522 (i.e., "start confirmation needed?"), if it is determined that a start confirmation is necessary, a flag is set to mark the state as "Not Started" at block 1524, and processing continues at block 1510.

If no start confirmation is needed, processing continues at block 1526 to mark state as already started. At decision block 1528 (i.e., "ready confirmation needed?"), if ready confirmation is needed, processing continues at block 1510. If it is not needed, the state is marked as already ready, and processing continues at block 1510.

At block 1510, an initial rowid range of each parallel table scan is obtained for each slave implementing the current DFO. At block 1512, an execution message is sent to all of the slaves that are implementing the current node. At block 1514, the current node is marked as started. Processing returns at block 1516.

#### SORCERER'S APPRENTICE

20

The present invention provides the ability to eliminate needless production of rows (i.e., the sorcerer's apprentice problem). In some cases, an operation is dependent on the input from two other operations. If the result of the first input operation does not produce any rows, there is no need for the second input generator to produce any rows. However, unless these input generators are aware of the fact that there is no need to continue processing, they will execute their operations.

- 40 -

For example, a sort/merge join operation is dependent on the output of two separate underlying operations. If the execution of the first underlying operation does not produce any rows, there is no need to execute any remaining operations in the sort/merge join task. However, unless the

5 processes executing the remaining underlying input are aware of the fact that there is no need to continue processing, they will continue to process despite the fact that there is no need to continue.

This problem is further complicated when multiple processes are

10 involved (e.g., multiple slaves performing the first table scan) because some of the processes may produce rows while others do not produce rows. Therefore, it is important to be able to monitor whether any rows are produced for a given consumer. The producers of the rows can't be used to perform the monitoring function because the producers are not aware of the other

15 producers or where the rows are going. Therefore, the consumer of the rows (i.e., the sort/merge join processes) must monitor whether any rows are received from the producers.

A bit vector is used to indicate whether each consumer process received

20 any rows from any producer slaves. Each consumer is represented by a bit in the bit vector. When all of the end of fetch ("eof") messages are received from the producers of a consumer slave, the consumer sends a done message to the data flow scheduler. The data flow scheduler determines whether the consumer slave received any rows, and sets the consumer's bit accordingly.

25 The bit in the bit vector is used by subsequent producers to determine whether any rows need to be produced for any of its consumers. The bit vector is reset at the beginning of each level of the tree.

- 41 -

Figure 9 illustrates a three way join. Employee table scan is implemented by slave DFOs 902A-902C in the first slave set. Rows produced by slave DFOs 902A-902C in the first set are used by the second slave set implementing the first sort/merge join (i.e., slave DFOs 906A-906C, respectively). The second set of input to sort/merge join slave DFOs 906A-906C is generated by department table scan slave DFOs 904A-906C in the first set, respectively. As slave DFOs 902A-902C complete, the sorcerer's apprentice bit vector is set to indicate whether any or none of slave DFOs 902A-902C produced any rows. If none of these slave DFOs produced any rows, there is no need to continue processing. Further, if slave DFOs 902A-902C did not produce any rows for consumer slave DFO 906C, there is no need for slave DFOs 904A-904C to send any output to consumer slave DFO 906C. Therefore, subsequent slave processes (e.g., 904C, 906C, 908C, or 910C) can examine the bit vector to determine what consumer slave DFOs should be serviced with input. The bit vector is updated to reflect a subsequent consumer slave's receipt (or lack thereof) of rows from their producer slaves, and examined by subsequent producer slave processes to determine whether to process rows for their consumer slaves.

## 20 PARALLELIZER EXECUTION

After a parallelizer has been initiated, its operations include synchronizing the parallel execution of the DFO tree. It allocates the DFOs in the DFO tree to the available slaves and specifies table queue information where appropriate. Like other row sources, the parallelizer row source can perform open, fetch, and close operations.

- 42 -

The data flow scheduler keeps track of the states of two DFOs at a time (i.e., the current DFO and the parent of the current DFO). As the slaves asynchronously perform the tasks, transmitted to them by the dataflow scheduler, they transmit state messages to the dataflow scheduler indicating the stages they reach in these tasks. The data flow scheduler tracks the number of slaves that have reached a given state, and the state itself. The counter is used to synchronize the slaves in a slave set that are performing a DFO. The state indicates the states of slaves implementing a DFO. For example, a started state indicates that a slave is started and able to consume rows. A ready state indicates that a slave is processing rows and is about to produce rows. A partial state indicates that a slave is finished with the range of rowids, and needs another range of rowids to process additional rows. Partial state is the mechanism by which slave processes indicate to the QC that they need another rowid range to scan. Done indicates that a slave is finished processing.

15

Some states are optional. The need for a given state is dependent on where the DFO is positioned in the DFO tree, and the structure of the DFO. All DFOs except the DFO at the top of the DFO tree must indicate when they are ready. Every DFO except the leaves of the DFO tree must indicate when they have started. A DFO that is a producer of rows reaches the ready state. Only table scan DFOs reach the partial state. A DFO that consumes the output of another DFO reaches the started state. Child DFOs that have a parent reach the done state.

25 -- Example --

Referring to Figure 3C, each dataflow scheduler starts executing the deepest, leftmost leaf in the DFO tree. Thus, the employee scan DFO directs its



- 43 -

underlying nodes to produce rows. Eventually, the employee table scan DFO is told to begin execution. The employee table scan begins in the ready state because it is not consuming any rows. Each table scan slave DFO SQL statement, when parsed, generates a table scan row source in each slave.

5

When executed, the table scan row source proceeds to access the employee table scan in the DBMS (e.g., performs the underlying operations required by the DBMS to read rows from a table), gets a first row, and is ready to transmit the row to its output table queue. The slaves implementing the table scan replies to the data flow scheduler that they are ready. The data flow scheduler monitors the count to determine when all of the slaves implementing the table scan have reached the ready state.

At this point, the data flow scheduler determines whether the DFO that is currently being implemented is the first child of the parent of this DFO. If it is, the data flow scheduler sends an execute to a second slave set to start the sort/merge join (SMJ) DFO (i.e., 324A-324C). The slaves executing the SMJ DFO (i.e., 324A-324C) will transmit a "started" message. When the data flow scheduler has received a "started" message from all of the SMJ slaves (i.e., "n" slaves where "n" is the number of table scan and SMJ slaves), the data flow scheduler sends a resume to the table scan slaves. When the table scan slaves receive the resume, they begin to produce rows.

During execution, the table scan slaves may send a partial message. A partial message means that a slave has reached the end of a rowid range, and needs another rowid range to scan another portion of the table. The data flow scheduler does not have to wait for the other table scan slaves to reach this state. The data flow scheduler determines whether any rowid ranges remain.

25

- 44 -

If there are no remaining rowid ranges, the data flow scheduler sends a message to the table scan slave that sent the "partial" message that it is finished. If there are more rowid ranges, the data flow scheduler sends the largest remaining rowid range to the table scan slave.

5

When each of the table scan slaves finish their portions of the scan, they send an "end of fetch" ("eof") message to the slaves that are executing the SMJ DFO via the table queue. When the SMJ DFO receives the "eof" messages from all of the table scan slaves, the SMJ DFO will report to the data flow scheduler that all of the table scan slaves are done. Once it is determined that all of the employee table scan has been completed, the data flow scheduler determines the next DFO to be executed.

The next DFO, the department table scan, is started. The same slave set is used to scan both the employee table and the department table. The department table scan slave DFOs (i.e., 344A-344C) will reach the ready state in the same way that the employee table scan reached ready. At that point, the data flow scheduler must determine whether the department table scan is the first child of its parent.

20

In this case, the department table scan DFO is not (i.e., the employee table scan DFO was the first child of the parent of the department table scan). Therefore, the parent DFO has already been started, and is ready to consume the rows produced by the department table scan slaves. Therefore, the data flow scheduler sends a "resume" to the department table scan slaves. The department table scan slaves will execute the department table scan sending "partial" messages, if applicable.

25

- 45 -

Once an "eof" message is received from all of the slaves implementing the department table scan, the SMJ DFO slaves can consume all of its inputs from the employee and department table scans, and will become ready to produce a row. At this point, the SMJ DFO slaves can transmit a "ready" message to the data flow scheduler.

Once the data flow scheduler receives a "ready" message from the all of the slaves (i.e., count is equal to the number of slaves implementing the SMJ DFO), the data flow scheduler must determine whether the SMJ DFO has parent. If so, the data flow scheduler must determine whether the SMJ DFO is the first child of its parent. If it is, the data flow scheduler must send a "execute" message to the slaves implementing the OrderBy DFO. In this case, the SMJ DFO is the first child of the OrderBy DFO (i.e., 322A-322C). Therefore, the data flow scheduler starts the OrderBy DFO. Because the set of slave that implemented the table scans are done, the OrderBy DFO can be implemented by the same set of slaves that implemented the table scan DFOs.

Once the OrderBy DFO has started, it sends a "started" message to the data flow scheduler. When the data flow scheduler has received "started" messages from all of the OrderBy DFO slaves, it can send a "resume" message to the SMJ DFO slaves. The SMJ DFO begins to produce rows for consumption by the OrderBy slaves. As each SMJ DFO finishes, they send "eof" messages to the OrderBy DFO. Once the OrderBy DFO receives an "eof" from all of the SMJ DFO slaves, the OrderBy DFO sends a message to the data flow scheduler. Because the OrderBy DFO is at the top of the tree, it does not have to go through any other states. Therefore, it can continue to output rows.

- 46 -

-- Fetch Operation --

When a data flow scheduler receives a request for one or more rows, it executes its fetch operation. Figure 11A illustrates a process flow for Fetch. At decision block 1102 (i.e., "current node not parallelized?"), if the current node is not parallelized, the row source operation is executed serially to satisfy the fetch request at block 1104. The data flow scheduler's fetch operation ends at block 1118.

10 If, at decision block 1102, it is determined that the current node is parallelized, processing continues at decision block 1106. At decision block 1106 (i.e., "does requester still want rows?"), if the requester no longer wants rows, processing ends at block 1118. If the requester still wants rows, processing continues at block 1110. At block 1110, the data flow scheduler waits for some  
15 output from the slaves processing the current node.

At decision block 1112 (i.e., "received some output from a slave?"), if one or more rows are output from the slaves processing continues at processing block 1116 to invoke ProcessRowOutput. If, at decision block 1112,  
20 the output is message output, processing continues at block 1114 to invoke ProcessMsgOutput. In either case, after the output is addressed, processing continues at decision block 1106 to determine if more rows are requested by the requester.

25 -- ProcessRowOutput --

When the data flow scheduler determines that slaves have generated rows (e.g., output rows to a TQ), the data flow scheduler monitors the output

- 47 -

using ProcessRowOutput. Figure 11B provides an example of the process flow of ProcessRowOutput. At block 1132, the output is accessed in the output TQ. At decision block 1134 (i.e., "eof" pulled from TQ?"), if the TQ output is an end of fetch, data flow scheduler marks all slaves as being finished, and stops the slaves at processing block 1136, and processing returns to Fetch at block 1144. If the output is not an "eof," processing continues at decision block 1138.

At decision block 1138 (i.e., "callback procedure supplied?"), if the requester supplied a callback routine to be used when rows have been produced, the data flow scheduler executes the callback routine, and processing returns to Fetch at block 1144. If there is no callback routine, processing continues at processing block 1142 to decrement the number of rows to be supplied, and the number of rows supplied. Processing returns to Fetch at block 1144.

15

-- ProcessMsgOutput --

The slaves executing the operations synchronized by the data flow scheduler send messages to the data flow scheduler to request additional direction, or to communicate their states. When the data flow scheduler receives these messages, it processes them using ProcessMsgOutput. Figure 11C illustrates a process flow of ProcessMsgOutput. At decision block 1162 (i.e., "Message = 'Started'?"), if the message received from a slave is "Started," processing continues at decision block 1164. If, at decision block 1164 (i.e., "all slaves started?"), the data flow scheduler has not received the "Started" message from all of the slaves processing returns to Fetch at 1188.

25

- 48 -

If the data flow scheduler has received the "Started" message from all of the slaves, processing continues at block 1166. At processing block 1166, the slaves' next state becomes "Ready," and the data flow scheduler specifies that none of the slaves have reached that state. After each slave has sent "Started" message to the data flow scheduler, they wait for a "Resume" message in return. At processing block 1168, the data flow scheduler sends a resume to the slaves, and processing returns to Fetch at block 1188.

If, at decision block 1162, the output was not a start message, processing continues at decision block 1170. At decision block 1170 (i.e., "Message = 'Ready?'"), if the output is a ready message, processing continues at block 1172 to invoke ProcessReadyMsg. After the ready message is processed by ProcessReadyMsg, processing returns to Fetch at block 1188.

If, at decision block 1170, the output was not a ready message, processing continues at decision block 1174. At decision block 1174 (i.e., "Message = 'Partial?'"), if the message was a "Partial," the slave has completed processing a table scan using a range, and is requesting a second range designation to continue scanning the table. At processing block 1176, the data flow scheduler sends a remaining range specification (if any) to the slave, and processing returns to Fetch at block 1188.

If, at decision block 1174, the message was not a partial message, processing continues at decision block 1178. At decision block 1178 (i.e., "Message = 'Done?'"), if the message is not a done message, processing returns to Fetch at 1188. If the message was a done message, processing continues at block 1180 to get the next DFO to be executed. At processing block 1182, the bit

- 49 -

vector is modified to record which consumers of the rows received rows from the finished slaves.

At decision block 1184 (i.e., "all slaves done and some DFO is started or started DFO is next of next's parent?"), processing continues at block 1186 to invoke NextDFO to begin the next DFO, and processing returns to Fetch at block 1188. If all of the slaves are not done or the started DFO is not ready, processing waits until the started DFO becomes ready, and returns to Fetch at block 1188.

10

-- Resume --

When a slave reports a ready for the current DFO, or a slave reports a started for the parent of the current DFO to the data flow scheduler, the data flow scheduler responds to the slave with a resume message to allow the slave to continue processing. Figure 12 illustrates a Resume process flow. At block 1202, the TQ ID for output, the TQ partitioning type, a node identifier, and the range partitioning keys are obtained. At decision block 1204 (i.e., "node executed by QC?"), if the node is being serially executed, processing continues at block 1206. At block 1206, the process implementing the node (e.g., QC, data flow scheduler) empties the entire row source into the appropriate TQ, and Resume ends at block 1212.

If, at decision block 1204, the node is parallelized, processing continues at block 1208 to send a resume message to all of the slaves executing the current node. The next state for the slaves is marked as "DONE," and the count of the number of slaves that have reached that state is set to zero at processing block 1210. Resume ends at block 1212.

— ProcessReadyMsg —

When a producer slave is about to produce rows, the producer slave  
5 sends a "Ready" message to the data flow scheduler. When a ready message is  
received by the data flow scheduler, the data flow scheduler processes the ready  
message using ProcessReadyMsg. Figure 13 illustrates a process flow for  
ProcessReadyMsg. At decision block 1302 (i.e., "all slaves ready?") if all of the  
slaves are not ready, processing returns to Fetch at 1318 to wait until all of the  
10 slaves reach the ready state.

If, at decision block 1302, it is determined that all of the states have  
reached ready (i.e., count is equal to the number of slaves), processing  
continues at processing block 1304. At block 1304, no DFO started is indicated.  
15 At decision block 1306 (i.e., "parent of current ready?"), if the parent of the  
current node is ready to receive the rows produced by the slaves implementing  
the current node, processing continues at decision block 1308.

At decision block 1308 (i.e., "is the current done?") if the slaves  
20 executing the current DFO have not reached the done state, processing returns  
to Fetch to wait for them to complete. If the slaves have reached the done  
state, NextDFO is invoked to implement the next node after the current DFO,  
and processing returns to Fetch at block 1318.

25 If, at decision block 1306 (i.e., "parent of current ready?"), the parent of  
the current is not ready, processing continues at 1310 to identify the parent of  
the current DFO. At decision block 1312 (i.e., "child first child of parent"), if the  
current node has a parent and the current node is the first child of the parent



- 51 -

to be executed, Start is invoked at block 1316 to start the parent. If the child is not the first child of the parent, the parent has already been started. Therefore, at block 1314, Resume is invoked to allow the parent to continue processing (e.g., consume the rows produced by the child). In either case, processing  
5 returns to Fetch at block 1318.

— NextDFO —

After the most recently process DFO reaches the done state, it is  
10 necessary to determine the next DFO to be executed. The pointers that implement the structure of the row source and DFO trees are used to identify the next DFO to be executed.

Generally, the row source tree is left deep. A row source tree is left deep,  
15 if any row source subtree is the subtree of only the left input to its enclosing row source subtree. However, it is possible for a row source tree to be right deep. When a done reply is received from all of the slaves, it is necessary to determine when to execute the next DFO. In a right-deep row source tree illustrated in Figure 5, the next DFO to execute after execution of current DFO  
20 502 is DFO 504 not parent DFO 506 even though current DFO 502 is the rightmost child of parent DFO 506. That is, next DFO 504 is not the parent of the current DFO 502. Thus, the normal next state (i.e., resume parent DFO 506) after receiving the done from current DFO 502. Therefore, it is necessary to wait until current DFO 502 is done, and parent DFO 506 has reached a stable,  
25 ready state. Once parent DFO 506 has reached a ready state, the message from the data flow scheduler is not a resume for parent DFO 506. Instead, the data flow scheduler transmits a message to execute next DFO 504, and to start DFO 508. When it is time to resume parent DFO 506, it is important to remember

- 52 -

that parent DFO 506 has already been started, and is waiting for a resume message. All of this is handled by NextDFO.

Figure 14 provides a process flow for NextDFO. At processing block 1402, the current node, the next node in the execution chain, the state of the parent, and the number of slaves executing the parent that have reached that state are identified. At processing block 1406, the sorcerer's apprentice bit vector is used to execute or resume, if the next DFO is a join apprentice (i.e., a DFO that needs to examine the join apprentice bit vector) to the current DFO.

10

At decision block 1408 (i.e., "is next a sibling of current?"), if the next DFO to be implemented is a sibling of the current DFO, processing continues at decision block 1412. If, at decision block 1408, the next DFO is not a sibling of the current DFO, the slave count for the parent is set to zero, and the parent's state is set to NULL at block 1410. Processing continues at decision block 1412.

15

At decision block 1412 (i.e., "does the next node have a child?"), if the next node does not have a child, the current DFO's state is set to NULL, and the number of slaves that have reached that state is set to zero at processing block 1414. At processing block 1416, Start is invoked to start next DFO. The next DFO is set to the current DFO at processing block 1433, processing returns at 1434.

20

If, at decision block 1412, the next node does have a child, processing continues at block 1418. At block 1418, parent is set to the parent of the next node. At decision block 1420 (i.e., "is next current's parent?"), if the next node is not the current's parent, the count is set to the number of slaves executing

25

- 53 -

the current node, and the state is set to the ready state. Processing continues at decision block 1426.

5 If, at decision block 1420, it is determined that next is current's parent, processing continues at block 1424 to set the state of the current node to the state of its parent, and to set the count for the number of slaves that have reached that state to the number of slaves implementing the parent that have reached that state. Processing continues at decision block 1426.

10 At decision block 1426 (i.e., "have all current's slaves reached the ready state?"), if all of the slaves implementing the current node have not reached ready, the next DFO is set to the current DFO at processing block 1433, and processing returns at block 1434. If all of the slaves are ready, processing continues at decision block 1428. At decision block 1428 (i.e., "does next have a  
15 parent and is next the first child of the parent?"), if next is the first child of its parent, Start is invoked at block 1432 to start parent. If next is not the first child of its parent, Resume is invoked at block 1430 to resume the parent. In either case, the next DFO is set to the current DFO at block 1433, and processing returns at block 1434.

20

— Close Operation —

The close operation terminates the query slaves. Close can occur when the entire row source tree has been implemented, or at the end of a DFO tree.  
25 Initially, the parallelizer sends a stop message to each of the slaves running DFOs in the parallelizer's DFO tree to tell each of the slaves to stop processing. This triggers the slaves to perform any clean up operations (e.g., release any

- 54 -

locks on data or resources) and to reach a state for termination. In addition, the close operation remits the slaves to the free pool.

Figure 16 illustrates a process flow for Close. At decision block 1601 (i.e.,  
5 "'Close' message expected by slaves?"), if a close message is expected by the slaves, SendCloseMsg at block 1604. Stop is invoked at block 1606. Flags are cleared at block 1608, and processing ends at block 1610.

Figure 17 illustrates a process flow for SendCloseMsg. At block 1702,  
10 DFO is set to the first executed DFO. At decision block 1704 (i.e., "no current DFO or current DFO not parallel?"), if there is not current DFO or the current DFO is not parallel, processing ends at block 1714. If not, processing continues at decision block 1706.

15 At decision block 1706 (i.e., "DFO found?"), if a DFO is not found, processing ends at block 1714. If a DFO is found, processing continues at decision block 1708. At decision block 1708 (i.e., "DFO slaves expecting close message?"), if the DFO is expecting a close message, processing continues at block 1710 to send a close message to each of the slaves in the set, and  
20 processing continues at decision block 1716. If the DFO is not expecting a close message, processing continues at decision block 1716.

At decision block 1716 (i.e., "DFO = current DFO?"), if the DFO is the current DFO, processing ends at block 1714. If it is not the current DFO, then  
25 processing continues at block 1716 to get the next DFO, and processing continues at decision block 1706 to process any remaining DFOs.

- 55 -

Figure 19 illustrates a Stop process flow. At decision block 1902 (i.e., "Serial process?"), if the process is a serial process, processing continues at block 1904 to close the underlying row source, and processing ends at block 1610. If the process is not a serial process, processing continues at block 1906.

5 At block 1906, the slaves are closed, and deleted, if necessary. At block 1908, current DFO and current output TQ are cleared. Processing ends at block 1610.

-- Row Operator --

10 The present invention provides the ability to pass a routine from a calling row source to an underlying row source. The routine can be used by the underlying row source to perform a function for the calling row source. For example, a calling row source can call an underlying row source and pass a routine to the underlying row source to place the row sources in a location for  
15 the calling row source. Once the underlying routine has produced the rows, the underlying row source can use the callback routine to place the row sources in a data store location (e.g., database or table queue).

### SLAVE PROCESSES

20

A slave DFO receives execution messages from the dataflow scheduler. For example, a slave DFO may receive a message to parse DFO SQL statements, resume operation, execute a DFO, or close. When a message is received by a slave DFO, the slave DFO must determine the meaning of the message and  
25 process the message. Figure 7A illustrates a process flow for receipt of execution messages.

- 56 -

At block 702, an execution message from the QC is read. At decision block 704 (i.e., "message is 'parse?'"), if the execution message is a parse message, processing continues at block 706 to invoke SlaveParse, and processing continues at block 702 to process execution messages sent by the QC.

- 5 If the execution message is not a parse message, processing continues at decision block 708. At decision block 708 (i.e., "message is 'execute?'"), if the execution message is an execute message, processing continues at block 710 to invoke SlaveExecute, and processing continues at block 702 to process execution messages.

10

- If, at decision block 708, the execution message is not an execution message, process continues at decision block 712. At decision block 712 (i.e., "message is 'resume?'"), if the execution message is a resume message, processing continues at block 714 to invoke SlaveResume, and processing continues at block 702 to process execution messages. If the message is not a resume message, processing continues at decision block 716. At decision block 716 (i.e., "message is 'close?'"), if the execution message is a close message, processing continues at block 718 to invoke SlaveClose. If the message is not a close message, processing continues at decision block 702 to process execution messages.
- 15
- 20

— SlaveParse —

- A parse execution message is sent after it is determined that the DFO SQL statements must be parsed before execution. Figure 7B illustrates a process flow for a slave DFO processing a parse message. At block 720, a database cursor is opened for each DFO. At block 722, each DFO SQL statement is parsed. Processing block 724 binds all SQL statement inputs and defines all
- 25

- 57 -

output values. At processing block 726, the parsed cursor numbers are returned to the QC, and the SlaveParse process ends.

-- SlaveExecute --

5

If an execute message is received from the QC, the slave DFO receiving the message must execute the DFO. Figure 7C illustrates a process flow for executing a DFO. At decision block 730 (i.e., first execute of this DFO?), if this is not the first execution message received for this DFO, processing continues at block 746 to invoke SlaveFetch to fetch all rows, and processing ends at block 748.

If this is the first execution message received, processing continues at decision block 732 (i.e., QC expects 'started?') to determine whether the QC expects a reply indicating that the slave has started. If yes, processing continues at block 734 to send a "started" message to the QC, and processing continues at block 736. If not, processing continues at block 736.

Block 736 processes bind variables, and executes the cursor. At block 738, a "done" replies are sent to QC for all of the child DFOs of the DFO being executed. At decision block 740 (i.e., "QC expects 'ready' replies?"), if the QC expects a ready message to indicate that the slave DFO is ready to fetch rows, processing continues at block 742. At block 742, one row is fetched from the DFO cursor. Processing continues at block 744 to send a "ready" reply to the QC, and processing ends. If the QC does not expect a ready message, processing continues at block 746 to fetch all rows from the DFO cursor, and processing ends at block 748.

- 58 -

**-- SlaveResume --**

After a slave DFO sends a ready message, it waits for a resume message from the QC to continue processing. When it receives a resume message, a  
5 slave DFO resumes its execution. Figure 7E illustrates a SlaveResume process flow. At decision block 750 (i.e., "first row already fetched?"), if the first row has already been fetched, processing continues at block 752 to write the first row to the slave DFO's output TQ, and processing continues at block 754. If the first row has not been fetch, processing continues at block 754. At block 754,  
10 SlaveFetch is invoked to fetch any remaining rows from the DFO cursor. Processing ends at block 756.

**-- SlaveClose --**

15 Upon completion of a DFO, the database cursor associated with the completed DFO can be closed. Figure 7E illustrates a process flow for SlaveClose. At block 762, the DFO's database cursor is closed. Processing ends at block 764.

**20 -- SlaveFetch --**

If a "ready" reply is not expected, or a slave DFO receives a resume after sending a "ready" reply, a slave DFO can fetch all the rows from a DFO cursor. Figure 7F illustrates a process flow to fetch all rows. At decision block 770 (i.e.,  
25 "given DFO cursor is at EOF?"), if the DFO cursor is at eof, processing continues at decision block 772.



- 59 -

At decision block 772 (i.e., "QC expects 'partial' reply?"), if a partial execution message is expected by the QC to indicate that the slave DFO has completed processing the range of rowids provided by the QC, processing continues at block 774 to send the partial message to the QC, and processing  
5 ends at 780. If a partial message is not expected (as determined at decision block 772), processing continues at block 778 to write an eof to the output TQ for the slave DFO. Processing ends at block 780.

If, at decision block 770 (i.e., given DFO cursor is at EOF?), it is  
10 determined that the DFO cursor is not at eof, processing continues at block 776 to fetch the next row from the DFO cursor. At block 782, the row is written to the slave DFO's output TQ, and processing continues at decision block 770 to fetch any remaining rows from the DFO cursor.

## 15 OTHER PARALLELIZATION EXAMPLES

One application for parallelism is the creation of an index. The index creation operation includes table scan, subindex create, and merge subindices operations. The table scan and subindex create can be performed in parallel.  
20 The output from the subindex creation operation is the input to the merge subindices process. In addition, a table can be created in parallel. A subtable create operation can create a table in parallel, and the subtables can be merged.

Thus, a method and apparatus for processing queries in parallel has  
25 been provided.

CLAIMS

- 
1. A method of implementing a database management system (DBMS) operation in parallel, independent of physical storage locations,  
5 including the steps of:  
generating a serial execution plan for an operation in said DBMS;  
generating a parallelized execution plan for said serial execution plan;  
executing said parallelized execution plan when a plurality of parallel  
resources of said computer system are available; and  
10 executing said serial execution plan when said plurality of resources are not available.
2. The method of claim 1 wherein said step of generating a parallelized execution plan includes the steps of:  
15 identifying one or more segments of said serial execution plan that can be parallelized; and  
identifying partitioning requirements of said serial execution plan.
3. The method of claim 1 wherein said step of generating a  
20 parallelized execution plan is based on a specification of parallelism in a statement specifying said operation.

- 61 -

4. A method of generating an execution plan to process a database management system (DBMS) operation in parallel including the steps of:

generating an execution plan for said operation;

examining said execution plan from the bottom up;

5 identifying a parallelized portion of said execution plan, said

parallelized portion can be processed in parallel;

identifying some serial portion of said execution plan, said serial portion can be processed in serial;

10 allocating a central scheduler between said parallelized portion and said serial portion.

5. The method of claim 4 further including the steps of:

identifying a first data flow requirement for a first portion of said execution plan;

15 identifying a second data flow requirement for a second portion of said execution plan; and

allocating a data flow director between said first portion and said second portion when said first data flow requirement is not compatible with said second data flow requirement.

20

6. A method of data access in a database management system including the steps of:

storing data on a plurality of storage devices, said plurality of storage devices are accessible by a plurality of computer systems;

25 examining a portion of said data; and

identifying one or more partitions for said data based on said examining of said portion such that each partition contains a share of said data.

- 62 -

7. A method of executing a database management system (DBMS) operation in parallel in a computer system, including the steps of:
- generating an execution plan to execute said operation in parallel;
  - initiating an operation coordinator in said computer system to
  - 5 coordinate execution of said execution plan;
  - initiating, by said operation coordinator, a first set of slaves to produce data;
  - initiating, by said operation coordinator, a second set of slaves to
  - consume data; and
  - 10 directing said second set of slaves to produce data and said first set of slaves to consume data when said first set of slaves finishes producing data.
8. The method of claim 7 wherein said execution plan is comprised of operator nodes and said operator nodes are linked together to form
- 15 execution sets.

- 63 -

9. A method of executing a database management system (DBMS) operation in parallel in a computer system, including the steps of:

generating an execution plan to execute said operation in parallel;

5 initiating a data flow scheduler in said computer system to coordinate data flow;

initiating, by said data flow scheduler, producer slaves to execute a first data production;

initiating, by said data flow scheduler, consumer slaves to consume said first data production;

10 transmitting a completion message to said data flow scheduler when said first data production is completed;

maintaining, by said data flow scheduler, an identification of a plurality of said consumer slaves that did not receive data in said first data production;

15 examining, by said producer slaves, said identification during a subsequent data production; and

reducing said subsequent data production such that said subsequent data production does not produce data for said plurality of said consumer slaves.

1/36




FIG. 1A




FIG. 1B

SUBSTITUTE SHEET (RULE 26)

2/36




FIG. 1C





FIG. 1D

3/36

FIG. 2





4/36




FIG. 3A

5/36




FIG. 3B

6/36





FIG. 3C

7/36

FIG. 4



8/36




FIG. 5

9/36

## FIG. 6A

DF0 Type	Type of DF0 (e.g., table scan, sort/merge join)
Pointer to Parent	Pointer to parent node
Pointer to Sibling	Pointer to next-node
Row Source	Row source equivalent for this node
Operation	
Table Queue Identifier	Identifies table queue for this node
Skipped Node Information	
Non-QC Node Information	
Pointer to First Child	Pointer to first child of parallelized node
Key Column Number	Number of key columns in input-table queue
Partitioning Type	Parallelized node's partitioning type (e.g., hash, key range, rowid range, round robin)
Clumped Columns	Number of clumped columns with parent
Predicates	
Control Blocks	
Table scan	Contains table scan information (e.g., table name and degree of parallelism)
Indexed Nested Loop Join	Contains information for an indexed nested loop join (e.g., right and left input table names)
Sort/Merge join	Contains information for a sort/merge join (e.g., merge or outer join control flags)
Index Creation	Contains information for index creation (e.g., column list, index type, and storage parameters)

10/36

## FIG. 6B

Pointer to Next-to-Execute	Pointer to next DFO to execute
Table Queue Identifier	Output table queue identifier
Rowid Table Number	Number of tables partitioned by rowid
SQL Statement Size	Size of SQL statement representing DFO
SQL Statement	SQL statement representing DFO
Flags	
Started	Slave sends "Started" message upon receipt
Ready	Slave sends "Ready" message when input consumed
Close	Slave expects to be closed upon completion

11/36





FIG. 7A



12/36

FIG. 7B



13/36

FIG. 7C




FIG. 7D






FIG. 7E



15/36

FIG. 7F



16/36




FIG. 8

17/36






FIG. 9

18/36




19/36


FIG. 10B(1)





20/36





22/36




FIG. 11A

23/36





FIG. 11B

24/36

FIG. 11C(1)



25/36




FIG. 11C(2)

26/36





FIG. 12

27/36


FIG. 13





28/36

FIG. 14(1)



29/36






FIG. 14(2)

30/36

FIG. 15(1)



31/36



32/36





FIG. 16

33/36

FIG. 17



34/36

FIG. 18(1)






FIG. 18(2)





36/36

FIG. 19



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US94/10092**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(6) :G06F 9/45

US CL :395/600, 700

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 395/600, 700

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS, ProQuest

search terms: query, parallel, query optimization

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Proceedings of the First International Conference on Parallel and Distributed Information Systems, IEEE, 1991, Wei Hong et al., "Optimization of Parallel Query Execution Plans in XPRS", pages 218-225, especially page 225.	1-9
X, P	US, A, 5,325,525 (SHAN ET AL) 28 June 1994, col. 5, lines 1-63.	1-9
A	US, A, 4,829,427 (GREEN) 09 May 1989, abstract.	1-9
A	US, A, 4,769,772 (DWYER) 06 September 1988, col. 3, lines 10-34.	1-9



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be part of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G*	document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means		
*P* document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

08 NOVEMBER 1994

Date of mailing of the international search report

16 FEB 1995

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-9565

Authorized officer

LARRY J. ELLCESSOR

Telephone No. (703) 305-3835

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US94/10092

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 5,091,852 (TSUCHIDA ET AL) 25 February 1992, col. 1, line 1 to col. 2, line 37.	1-9

**THIS PAGE BLANK (USPTO)**